

IN THE CLAIMS

Please amend the claims as follows:

1-62 (Canceled).

63 (Currently Amended): An electrostatic actuation device comprising:

at least one mobile electrode, comprising at least one ~~mobile part~~ membrane that is flexible and free to move with respect to a substrate, and an electrical contact element fixed on the ~~mobile part~~ membrane;

at least two fixed electrodes, fixed with respect to the substrate, wherein the at least two fixed electrodes are located on a same side of the mobile electrode and each facing the ~~mobile part~~ membrane of the mobile electrode; and

means for forming at least one pivot of at least one portion of the mobile electrode, said means forming at least one pivot being disposed directly under the ~~mobile part~~ membrane that is flexible and free to move,

wherein each of the at least two fixed electrodes are configured to progressively force the ~~mobile part~~ membrane of the mobile electrode facing each of the fixed electrodes, respectively, to contact the substrate as a function of applied voltage, and

the ~~mobile part~~ membrane bears directly on the means forming at least one pivot when only one of the fixed electrodes attracts a first portion of the ~~mobile part~~ membrane of the mobile electrode facing the fixed electrode, and another portion of the ~~mobile part~~ membrane of the mobile electrode is configured to move away from the substrate by mechanical return forces, thereby moving the electrical contact between a high position and a low position.

64 (Currently Amended): A device according to claim 63, wherein the at least one ~~mobile part~~ membrane extends along at least one direction perpendicular to the substrate.

65 (Previously Presented): A device according to claim 63, wherein the at least two fixed electrodes are separated from the mobile electrode by an insulating layer.

66 (Canceled).

67 (Previously Presented): A device according to claim 63, wherein the means for forming the at least one pivot includes at least one pad fixed with respect to the substrate.

68 (Withdrawn and Currently Amended): A device according to claim 63, wherein the means for forming the at least one pivot includes at least one arm arranged laterally with respect to the ~~mobile part~~ membrane, or two arms arranged on each side of the ~~mobile part~~ membrane.

69 (Withdrawn and Currently Amended): A device according to claim 63, wherein the ~~mobile part~~ membrane of the mobile electrode forms an elbow.

70 (Withdrawn and Currently Amended): A device according to claim 63, comprising four fixed electrodes arranged in pairs facing each other, the mobile electrode comprising two ~~mobile parts~~ membranes arranged crosswise.

71 (Withdrawn): A device according to claim 70, comprising two pivots.

72 (Previously Presented): A device according to claim 65, wherein the mobile electrode comprises at least one part embedded or fixed on or in the substrate or the insulating layer.

73 (Previously Presented): A device according to claim 63, wherein each fixed electrode is disposed to face at least one end of the mobile electrode, on one side of the means for forming the at least one pivot.

74 (Currently Amended): A device according to claim 63, wherein the mobile electrode comprises at least two ~~mobile parts~~ membranes, each ~~mobile part~~ membrane being free at one of its ends.

75 (Withdrawn and Currently Amended): A device according to claim 74, wherein the mobile electrode comprises three ~~mobile parts~~ membranes, and the device includes three electrodes that are fixed and disposed to face the three ~~mobile parts~~ membranes.

76 (Withdrawn and Currently Amended): A device according to claim 74, wherein each ~~mobile part~~ membrane of the mobile electrode is elongated, and laterally or angularly offset from each other.

77 (Withdrawn): A device according to claim 63, comprising three fixed electrodes, and the mobile electrode includes three strips connected through an end.

78 (Currently Amended): An electrostatic actuation device comprising:

a ~~mobile-part~~ membrane that is flexible and free to move with respect to a substrate, the ~~mobile-part~~ membrane including at least two electrodes, separated by an electrically insulating portion, and an electrical contact element fixed on the ~~mobile-part~~ membrane;

at least one fixed electrode, fixed with respect to the substrate, ~~wherein the at least one fixed electrode is located on a same side of the mobile-part~~, the at least one fixed electrode including a first part and a second part disposed to face a corresponding one of the electrodes of the ~~mobile-part~~ membrane; and

means for forming at least one pivot of at least one portion of the ~~mobile-part~~ membrane, said means forming at least one pivot being disposed directly under the ~~mobile-part~~ membrane that is flexible and free to move,

wherein each of the first part and the second part of the at least one fixed electrode is configured to progressively force the corresponding electrode of the at least two electrodes in the ~~mobile-part~~ membrane to contact the substrate as function of applied voltage, and

the ~~mobile-part~~ membrane bears directly on the means forming at least one pivot when the at least one fixed electrode attracts only one of the electrodes of the ~~mobile-part~~ membrane, the other electrode of the ~~mobile-part~~ membrane being free to move away from the substrate by mechanical return forces, thereby moving the electrical contact between a high position and a low position.

79 (Currently Amended): A device according to claim 78, wherein the ~~mobile-part~~ membrane is free to move along at least a direction perpendicular to the substrate.

80 (Currently Amended): A device according to claim 78, wherein the at least one fixed electrode is separated from the ~~mobile-part~~ membrane by an insulating layer.

81 (Canceled).

82 (Previously Presented): A device according to claim 78, wherein the means forming the pivot comprises at least one pad fixed with respect to the substrate.

83 (Withdrawn and Currently Amended): A device according to claim 78, wherein the means for forming the pivot comprises at least one arm arranged laterally with respect to the ~~mobile part~~ membrane, or two arms arranged on each side of the ~~mobile part~~ membrane.

84 (Withdrawn and Currently Amended): A device according to claim 78, wherein the ~~mobile part~~ membrane forms an elbow.

85 (Withdrawn and Currently Amended): A device according to claim 78, wherein the at least one fixed electrode includes four fixed electrodes arranged in pairs facing each other, the ~~mobile part~~ membrane comprising two ~~mobile parts~~ membranes arranged crosswise.

86 (Withdrawn): A device according to claim 85, wherein the at least one pivot includes two pivots.

87 (Currently Amended): A device according to claim 80, wherein the ~~mobile part~~ membrane comprises at least one part embedded or fixed on or in the substrate or the insulating layer.

88 (Currently Amended): A device according to claim 78, wherein the at least one fixed electrode is disposed to face at least one end of the ~~mobile part~~ membrane, on one side of the means for forming the at least one pivot.

89 (Withdrawn and Currently Amended): A device according to claim 78, wherein the ~~mobile part~~ membrane comprises at least two mobile electrodes connected at one end by an insulating portion, each mobile electrode being free at one of its ends, and the device further comprises fixed electrodes disposed to face each mobile electrode.

90 (Withdrawn and Currently Amended): A device according to claim 89, wherein the ~~mobile part~~ membrane comprises three mobile electrodes.

91 (Withdrawn): A device according to claim 89, wherein the mobile electrodes are elongated and laterally or angularly offset from each other.

92 (Previously Presented): A device according to claim 78, wherein the at least one fixed electrode includes at least two fixed electrodes.

93 (Canceled).

94 (Withdrawn): A device according to claim 63, wherein the mobile electrode, the fixed electrodes, and the means forming the pivot are in a plane on a surface of the substrate.

95 (Withdrawn): A device according to claim 63, wherein the at least one mobile electrode comprises at least one magnetic or partially magnetic element, and the device

further comprises at least one fixed magnetic or partially magnetic element, fixed with respect to the substrate, which attract each other.

96 (Withdrawn and Currently Amended): A device according to claim 95, wherein an electrostatic force and magnetic force involved during said contact of said ~~mobile part~~ membrane with said substrate has a relative difference of at least 10%.

97 (Withdrawn and Currently Amended): A device according to claim 95, wherein an electrostatic force and magnetic force involved during said contact of said ~~mobile part~~ membrane with said substrate is greater than the mechanical return forces.

98 (Withdrawn and Currently Amended): A device according to claim 97, wherein an electrostatic force and magnetic forces involved during said contact of said ~~mobile part~~ membrane t with said substrate are at least 10 times greater than the mechanical return forces.

99 (Withdrawn): A device according to claim 95, wherein the at least one magnetic or partially magnetic element and the at least one fixed magnetic or partially magnetic element define at least two stable intermediate positions of the device between the high position and the low position.

100 (Canceled).

101 (Previously Presented): A device according to claim 63, wherein the means for forming the pivot holds a point of the mobile electrode at a height of between 50 nm and 20 μ m with respect to the substrate.

102-124 (Canceled).

125 (Previously Presented): A device according to claim 63, wherein said electrical contact element closes a circuit when it is in the low position.

126 (Previously Presented): A device according to claim 63, wherein said electrical contact element comes into contact with a track of a circuit when it is in the low position.

127 (Withdrawn): A device according to claim 95, wherein said magnetic or partially magnetic elements hold the electrical contact in the high and low positions.

128 (Withdrawn): A device according to claim 63, wherein said electrical contact element forms an armature, the device includes another armature being fixed with respect to said substrate, and said armatures form a variable capacitor.

129 (Withdrawn): A device according to claim 128, wherein said variable capacitor has continuous operations between said high and said low positions.

130 (Withdrawn): A device according to claim 128, wherein said variable capacitor has stable positions between said high and said low positions.

131 (Previously Presented): A device according to claim 78, wherein said electrical contact element closes a circuit when it is in the low position.

132 (Previously Presented): A device according to claim 78, wherein said electrical contact element is in contact with a track of a circuit when it is in the low position.

133 (Withdrawn): A device according to claim 78, wherein the at least one mobile electrode comprises at least one magnetic or partially magnetic element and the device further comprises at least one fixed magnetic or partially magnetic element fixed with respect to the substrate, which attract each other.

134 (Withdrawn and Currently Amended): A device according to claim 133, wherein an electrostatic force and magnetic forces involved during said contact of said ~~mobile part~~ membrane with said substrate has a relative difference of at least 10%.

135 (Withdrawn and Currently Amended): A device according to claim 133, wherein an electrostatic force and magnetic forces involved during said contact of said ~~mobile part~~ membrane with said substrate are greater than the mechanical return forces.

136 (Withdrawn and Currently Amended): A device according to claim 135, wherein an electrostatic force and magnetic forces involved during said contact of said ~~mobile part~~ mobile part membrane with said substrate are at least 10 times greater than the mechanical return forces.

137 (Withdrawn): A device according to claim 133, wherein the at least one magnetic or partially magnetic element and the at least one fixed magnetic or partially magnetic element define at least two stable intermediate positions of the device between the high position and the low position

138 (Withdrawn): A device according to claim 133, wherein said magnetic or partially magnetic elements hold the electrical contact element in the high and low positions.

139 (Previously Presented): A device according to claim 78, wherein said electrical contact element forms an armature, the device including another armature being fixed with respect to said substrate, and said armatures forming a variable capacitor.

140 (Previously Presented): A device according to claim 139, wherein said variable capacitor has continuous operations between said high and said low positions.

141 (Previously Presented): A device according to claim 139, wherein said variable capacitor has stable positions between said high and said low positions.